


# CAMPLEX®

## BROADCAST FIBER OPTIC SOLUTIONS

### Complex CMX-3GSDI-TR SDI Single Mode Converter Extender


#### CMX-3GSDI-TR TRANSMITTER

- 1 SDI Input—Connect to Source
- 2 Link LED
- 3 Signal LED
- 4 Power LED
- 5 Fiber Connection
- 6 Power Adapter Connection




#### CMX-3GSDI-TR RECEIVER

- 1 SDI Output — Connect to Display
- 2 Link LED
- 3 Signal LED
- 4 Power LED
- 5 Fiber Connection
- 6 Power Adapter Connection



#### SYSTEM SET UP



#### SPECIFICATIONS

Compliance	3G/HD/SD SDI
Transmission Distance	6.2 Miles ST Single Mode
Signal Level	800mVp-p +/- 50mV
Max Resolution	1080p@60Hz
Video Bandwidth	3 Gbps
Supports	SMPTE-292M(HD-SDI), SMPTE- 259M(SD-SDI), SMPTE-424M(3G-SDI)
Dimensions	3.25 x 0.75 x 0.63 in (with connectors)   1.95 x 0.75 x 0.63 (without connectors)
Weight	0.36 lb

#### Includes

- Two 5DC/2A Power Supplies
- One 3G-SDI Transmitter
- One 3G-SDI Receiver

