

CMX-X3Q04M Datasheet

The Camplex CMX-X3Q04M is a tactical assembly that features the QPC's QFoca Hermaphroditic Tactical Connector Line engineered for Harsh Environment and Military Ground Tactical applications. QFoca connectors are suitable for various applications, including Military Ground Tactical, Aerospace Ground Communications, Oil & Gas, Mining, Factory Automation, Heavy Equipment, Broadcast, Audio/Video, and Sensing Applications. Available in Single Mode and Multimode, and a variety of lengths.

Features:

- 4 Channel Hermaphroditic Physical Contact Connector System
- Designed to MIL-DTL-83526/16 (Plug) & MIL-DTL-83526/17 (Jam Nut Receptacle)
- QFoca Intermateability: Amphenol TFOCA-II, OCC TFOCA 2, Delphi DFOCA, Glenair GFOCA
- Sealed to IP68 Rating
- Lightweight MIL-Tactical Cable Ideal for use in Harsh Environments Where Deployment and Retrieval for Reuse are Required



CMX-X3Q04M



CMX-X3Q04MR

CMX-X3Q04M Datasheet

Specifications:

Complex Tactical OM4 Multimode Fiber:

- **Fiber Type:** Laser Optimized Bend Tolerant OM4
- **Core/Cladding Diameter (µm):** 50/125
- **Numeric Aperture:** 0.2
- **Wavelength (nm):** 850/1310
- **Gigabit Ethernet Distance (m):** 1040/600
- **10-Gigabit Ethernet Distance (m):** 550/300
- **Maximum Cables Attenuation (dB/km):** 3.0/1.0
- **Minimum Laser EMB Bandwidth (MHz-km):** 4700/500
- **Minimum OFL LED Bandwidth (MHz-km):** 3500/500
- **Primary Coating Diameter (µm):** 245
- **Secondary Coating Diameter (µm):** 900
- **Proof Test Level (kpsi):** 100
- **Jacket Material:** Polyurethane
- **Buffer Material:** Hard Elastomeric
- **Cable Diameter:** 0.22in (5.5mm)
- **Impact Resistance:** 1500 impacts
- **Crush Resistance:** 1800 N/cm
- **Flex Resistance:** 2000 cycles
- **Max Tensile Load:**
 - Installation: 1,800 N (400 lbs)
 - Operating: 600 N (130 lbs)
- **Min Bend Radius:**
 - Installation: 2.2in (5.5cm)
 - Operating: 1.1in (2.8cm)
- **Temperature:**
 - Operating: -40°F to 185°F (-40°C to +85°C)
 - Storage: -94°F to 185°F (-70°C to +85°C)

QPC QFoca Connectors:

- **Insertion Loss:** 0.10-0.75dB Max. (0.30dB Typical)
- **Lifetime:** 2000 Cycles
- **IP Rating:** IP68 - Dust Tight; No ingress of dust; complete protection against contact; Water Immersion Beyond 1 Meter
- **Vibration Resistance:** 10 to 2000Hz / 15g EIA/TIA-455-11; Cond. III
- **Impact Resistance:** 8 Impacts @ 8FT (2.4MT); EIA/TIA-455-2
- **Shock Resistance:** 50g for 11ms; EIA/TIA-455-14; Condition A