

CMX-TL-1604

Fiber Video Inspection Scope with LCD Display and Rugged Carrying Case

Features:

- Portable Fiber Inspection Scope
- Convenient Focus Control Knob
- Hand Held LCD Display with Brightness Control
- Great for Hard-to-reach Connectors on the Backside of Patch Panels
- Includes 6 Fiber Adapter Tips
- Rugged Carrying Case

Specifications:

- Magnification: 250x (3.5" Monitor)
- Resolution Ratio: 0.5µm
- Display: 3.5" TFT-LCD, 960x240 pixels
- Video Output: NTSC/PAL
- Power Supply: 3.7V, 4500mA 5V1A Rechargeable Li Battery
- Weight: 3.31 lbs (1.5 kg)
- Operating Temperature: -4°F - 122°F (-20°C - 50°C)
- Storage Temperature: -22°F - 140°F (-30°C - 60°C)
- **Adapter Type & Description:**
- 25-U-M (2.5mm UPC Male) - FC/SC/ST/E2000 - Patch Cord UPC Termination
- 125-U-M (1.25mm UPC Male) - LC/MU Patch Cord UPC Termination
- 25-A-M (2.5mm APC Male) - FC/SC/ST/E2000 - Patch Cord APC Termination
- 125-A-M (1.25mm APC Male) - LC/MU Patch Cord APC Termination
- 25-U-F (2.5mm UPC) - FC/SC/ST/E2000 - UPC Bulkhead

Item Includes:

- 1 x CMX-TL-1604 Inspection Probe
- 1 x LCD 3.5" Monitor
- 1 x Rugged Carrying Case
- 1 x 3.7V, 4500mA 5V1A Rechargeable Li Battery
- 1 x Battery Charger
- 1 x TIP-U-1.25 - CMX-TL-1604-1
- 1 x TIP-U-2.5 - CMX-TL-1604-2
- 1 x TIP-A-1.25 - CMX-TL-1604-3
- 1 x TIP-A-2.5 - CMX-TL-1604-4
- 1 x TIP-C-1.25 - CMX-TL-1604-5
- 1 x TIP-C-2.5 - CMX-TL-1604-6



Commitment to Engineering Excellence

Our objective is to maintain engineering excellence in fiber optic cable and transport system manufacturing with a 100% inspection and zero-defect policy performed by trained and certified assemblers, as well as an R&D laboratory dedicated to the latest technology compliance testing. We strive for exceptional quality every day to ensure your confidence in our products and in our commitment to your success.