

CMX-TROCMTPM Datasheet

The Camplex CMX-TROCMTPM is a ruggedized OM3 multimode fiber trunk cable designed for crews who need fast, reliable fiber deployment in uncontrolled outdoor environments and high-density data transport applications where a single, manageable cable run must carry multiple simultaneous single paths. By consolidating 12 fibers into one compact assembly terminated with Neutrik opticalCON MTP connectors, it eliminates the connector count, cleaning burden, and installation time associated with individual fibers.

Features:

- Outdoor Field Deployable
- Low Insertion Loss and Optimized Optical Return Loss Values
- Space-Saving Multi-Fiber Design Reduces Cleaning and Mating Time
- Bend Optimized and Laser Optimized OM3 Multimode Fiber Cable
- Neutrik opticalCON MTP Connectors are IP65-rated in Mated Condition



CMX-TROCMTPM Datasheet

Specifications:

OM3 Multimode Fiber Cable:

- **Fiber Type:** OM3 Multimode
- **Core/Cladding Diameter (μm):** 50/125
- **Number of Fibers:** 12
- **Primary Coating Diameter (μm):** 280
- **Secondary Buffer Diameter (μm):** 900
- **Numerical Aperture:** 0.2
- **Proof Test Level (kpsi):** 100
- **Wavelength (nm):** 850/1300
- **Gigabit Ethernet Distance (m):** 1000/550
- **Attenuation (dB/km):** 3.0/1.0
- **Bandwidth (MHz-km):** 1500/500
- **Jacket Material:** Polyurethane
- **Cable Diameter:** 0.3in (8.2mm)
- **Crush Resistance:** 30 N/cm
- **Min. Bend Radius:**
 - Installation: 3.2in (82mm)
 - Operation: 1.2in (33mm)
- **Max. Tensile Load:**
 - Installation: 600 N
 - Operation: 600 N
- **Temperature:**
 - Operation: -67°F to 185°F (-55°C to +85°C)
 - Storage: -94°F to 185°F (-70°C to +85°C)

Neutrik opticalCON MTP Connector:

- **Insertion Force:** < 45 N
- **Withdrawal Force:** < 45 N
- **Insertion Loss:** < 0.9 dB / connection
- **Lifetime:** 2500 mating cycles
- **Optical Wiring:** Method A
- **Protection Class:** IP65 in mated condition