

## HF-FUWPUW-M Datasheet

Complex's HF-FUWPUW-M series of SMPTE 304M/311M outside broadcast camera cables feature LEMO FUW and PUW connectors and Furukawa's harsh environment cable. Designed for on-the-go deployments, from remote production trucks and camera-side connections to stadiums and production facilities. This series integrates a power line for the TV camera, a control line, and an optical fiber for video and audio transmission.

### Features:

- Premium Furukawa Outside Broadcast Cable & LEMO Connectors
- Meets or Exceeds SMPTE 304M/311M Standards
- Terminations by LEMO Trained Technicians
- Electrical Assemblies 100% Tested for Continuity and Shorts
- Fiber Optic Assemblies 100% Tested for Attenuation and Back Reflection
- Rubber Dust Caps



## HF-FUWPUW-M Datasheet

### Specifications:

#### Furukawa 9.2mm SMPTE 311M Hybrid Cable:

- **Fiber Type:** Single Mode
- **Core/Cladding Diameter (µm):** 9/125
- **Conductor Resistance:**
  - Power Line: 37.5Ω/km
  - Control Line: 113Ω/km
- **Insulation Resistance:** 10,000MΩ·km
- **Withstand Voltage:** AC1,750V/1min.
- **Strength Member Material:** Steel wire
- **Shield Material:** Tin-plated soft copper wire braid
- **Sheath (PB-Free):** Abrasion-Resistant Sheath
- **Finished Outside Diameter:** 0.36in (9.2mm)
- **Allowable Tension:** 700N
- **Bend Radius:** 2.17in (55.2mm)

#### LEMO Connectors:

- **Number of Contacts (Low Voltage):** 2
- **Number of Contacts (High Voltage):** 2
- **Number of Contacts (Fiber Optic):** 2
- **Rated Current:** 10A
- **Vtest Power/Signal (AC):** 2250V, 1000V
- **Working Voltage Power/Signal (AC):** 600V, 42V
- **IP Rating:** IP68
- **Lifetime:** 2000 Mating Cycles
- **Shielding (min):** 95 dB (10 MHz)
- **Shielding (min):** 80 dB (1 GHz)
- **Shock Resistance:** 100g [6 ms]
- **Vibration Resistance:** 15g [10 Hz - 2000 Hz]