

HF-TS12ST-XXX Datasheet

The Camplex HF-TS12ST 12-Channel ST-Single Mode Fiber Optic Tactical Assembly is a highly rugged and lightweight tactical snake, ideal for Touring, Broadcast, Rental houses, Live Event Production, Military Field use, Commercial Applications and more. The HF-TS12ST utilizes a tactical breakout to ensure the weakest area of a cable, the breakout, remains rugged and reliable, with an aluminum body and individual tactical 36-inch fanout legs for added protection. The OCC 12 Channel tactical fiber uses a polyurethane jacket and "Core-Locking" jacket that provides resistance to chemicals, crushing forces, cutting forces, and harsh environments. The HF series from Camplex is a premium tactical cable built to exceed the requirements of rigorous field use.

Features:

- OCC's 12-channel Low Water Peak Tactical Single-Mode Optic Fiber is outdoor-rated, chemical-resistant, crush-resistant, impact-resistant, and cut-resistant.
- Core-locked jacket reinforces the cable's core and additional crush and impact protection and tear resistance during installation.
- Helically Stranded Cable core for increased flexibility and protection.
- IP50-rated Breakout kit with 36-inch fanouts
- Individual fanout channels protected with 3mm riser-rated tactical furcation tubing





HF-TS12ST-XXX Datasheet

Specifications:

- Fiber Type: Low Water Peak Single Mode
- Cable Diameter: 0.26in (6.5mm)
- Jacket Material: Polyurethane
- Buffer Material: Hard Elastomeric
- Core/Cladding Diameter: 9/125 μm
- Maximum Cabled Attenuation: 0.5 dB/0.5 km
- Max Tensile load (Installation):2100 N (470lbs)
- Max Tensile load (Operating): 700 N (160lbs)
- Min Bend Radius (Installation): 2.6in (6.5cm)
- Min Bend Radius (Operating): 1.3in (3.3cm)
- Crush-Resistant (TIA/EIA-455-41A, Military Reg): 200 impacts
- Impact Resistance (EIA/TIA-455-25A, Military Reg): 440 N/cm
- Cable Weight: 0.028lbs/ft (0.04kg/m)
- Operating Temperature: -67°F-185°F (-55°C to +85°C)